



General Purpose Handheld Linear Imager Bar Code Reader with Datalogic's STAR Cordless System™

The Gryphon family represents the premium line of Datalogic Scanning's general purpose handheld data collection products. The Gryphon GM4100 cordless linear imaging readers offer the richest feature set among general purpose product offerings.

Extremely versatile and durable, the Gryphon GM4100 cordless linear imaging readers are the ultimate solution for applications in retail and light industrial environments where mobility is necessary for improved productivity. Mobile communications also eliminate the restraints caused by cabled devices, providing a safer and more efficient environment for employees.

Narrow band radio communications with Datalogic's STAR Cordless System™ is the key to increased productivity and flexibility in the workplace. The GM4100 reader series offer scalable solutions from simple point-to-point applications to networking capabilities combined with seamless roaming for complex installations. An optional display with a 3-button keypad provides battery status, radio coverage indicator and enables operator interaction with the host system.

Datalogic's new, patented 2-position cradle provides multiple solutions to answer different functional and reduced space requirements. It provides hands-free reading capabilities and a scan-while-charging feature to ensure constant up-time for increased productivity.

GM4100 Batch Mode capability allows thousands of codes to be stored in memory. This feature combined with a long lasting 50K scans per charge Lithium-Ion battery allows unlimited mobility and reliable data collection when out-of-range from the base station.

Featuring Datalogic's exclusive patented 'Green Spot' for good read feedback directly on the code, it helps to improve productivity especially in noisy environments. When using the product with the cradle at a 45° position, the Green Spot can work as an aiming system remaining on to aid in positioning the code for quick and intuitive reading.

Standard multi-interface capabilities (GM4130) provide host connectivity via USB, RS-232, Keyboard Wedge and Wand Emulation while IBM interface models (GM4110) provide connectivity via IBM 46XX, USB and RS-232 emulation. The Datalogic Aladdin™ configuration program provides user-friendly features that simplify the start-up procedure, even for inexperienced users.



Features

- Fastest speed-to-read - 325 reads/second
- Radio frequencies available in 433 MHz or 910 MHz
- Radio Range (open air) up to 30.0 m / 98.4 ft for 433 MHz, up to 15.0 m / 49.2 ft for 910 MHz
- Optional display with 3-Key keypad
- Point-to-point and multi-point transmission
- Datalogic's patented 2-position cradle with Scan-While-Charging capability
- Batch Mode capability (>1200 codes stored in memory)
- Drop resistance to 1.8 m / 5.9 ft
- Datalogic's patented 'Green Spot' for good-read feedback
- Long lasting user-replaceable Lithium-Ion battery

Specifications

CORDLESS COMMUNICATIONS

DATALOGIC STAR CORDLESS SYSTEM™

Effective Radiated Power: 433.92 MHz: < 10 mW; 910 MHz: < 1 mW
 Multi-Point Configuration: Max. Readers in Same Area: 2048
 Max. Readers per Radio Receiver: 16
 Point-to-Point Configuration
 Radio Frequency: 433.92 MHz; 910 MHz
 Radio Range (Open Air): 433.92 MHz: 30.0 m / 98.4 ft
 910 MHz: 15.0 m / 49.2 ft
 Seamless Roaming
 Two Way Communications

DECODING CAPABILITY

1D / LINEAR CODES

Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes

POSTAL CODES
 STACKED CODES

China Post
 GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional

ELECTRICAL

BATTERY

Battery Type: Lithium-Ion, 2100 mAh
 Charge Time: External Power: 4 Hours
 Reads per Charge: 50,000
 Battery Charging (Red); Charge Completed (Green); Power/Data (Yellow)
 Charging (Typical): < 8 W; Operating (Typical): < 2.5 W @ 5 VDC;
 Standby/Idle (Typical): < 2.5 mA @ 5 VDC
 4.75 - 14 VDC +/- 5%

CRADLE INDICATOR LEDS

CURRENT

INPUT VOLTAGE

ENVIRONMENTAL

AMBIENT LIGHT
 DROP RESISTANCE

100,000 lux
 Withstands repeated drops from 1.8 m / 5.9 ft onto a concrete surface
 16 kV
 5 - 95%
 IP52
 Operating: 0 to 50 °C / 32 to 122 °F
 Storage/Transport: -20 to 70 °C / -4 to 158 °F

ESD PROTECTION (AIR DISCHARGE)
 HUMIDITY (NON-CONDENSING)
 PARTICULATE AND WATER SEALING
 TEMPERATURE

INTERFACES

RS-232 / IBM 46XX / USB Multi-Interface
 RS-232 / USB / Keyboard Wedge / Wand Multi-Interface

PHYSICAL CHARACTERISTICS

COLORS AVAILABLE
 DIMENSIONS

DISPLAY

KEYPAD
 WEIGHT

Black; White
 Cradle: 18.6 x 9.9 x 5.6 cm / 7.3 x 3.9 x 2.2 in
 Reader: 18.1 x 7.1 x 10.0 cm / 7.1 x 2.8 x 3.9 in
 Display Type: GM4100-D Only: Graphic with backlight
 Font Dimensions: User selectable (4 lines x 16 columns default)
 Screen Dimensions: 32 x 96 pixels
 GM4100-D Only: 3-Key Keypad
 Cradle: 246.0 g / 8.7 oz; Reader (with Display): 246.0 g / 8.7 oz

READING PERFORMANCE

LIGHT SOURCE
 PRINT CONTRAST RATIO (MINIMUM)
 READ RATE (MAXIMUM)
 READING ANGLE
 READING INDICATORS

Illumination: LED Array 630 - 670 nm
 15%
 325 reads/sec.
 Pitch: +/- 65°; Roll (Tilt): +/- 35°; Skew (Yaw): +/- 65°
 Beeper (Adjustable Tone and Volume); Datalogic 'Green Spot' Good Read Feedback; Good Read LED
 0.076 mm / 3 mils

RESOLUTION (MAXIMUM)

READING RANGES

TYPICAL DEPTH OF FIELD

Minimum distance determined by symbol length and scan angle.
 Printing resolution, contrast, and ambient light dependent.
 5 mils: 6.0 to 18.0 cm / 2.3 to 7.0 in
 7.5 mils: 3.5 to 30.0 cm / 1.4 to 11.7 in
 10 mils: 2.0 to 45.0 cm / 0.8 to 17.7 in
 13 mils: 3.0 to 60.0 cm / 1.2 to 23.4 in
 20 mils: 3.0 to 80.0 cm / 1.2 to 31.2 in

SAFETY & REGULATORY

AGENCY APPROVALS

The product meets necessary safety and regulatory approvals for its intended use.
 The Quick Reference Guide for this product can be referred to for a complete list of certifications.
 Complies to China RoHS; Complies to EU RoHS
 IEC 60825-1 Class 1 LED Product

ENVIRONMENTAL COMPLIANCE
 LED CLASSIFICATION

UTILITIES

DATALOGIC ALADDIN™

Datalogic Aladdin configuration program is available for download at no charge

OPOS / JAVAPOS
 REMOTE HOST DOWNLOAD

OPOS Utilities are available for download at no charge
 Lowers service costs and improves operations: BC4010

WARRANTY

3-Year Factory Warranty

Base Stations/Chargers

- BC4010: Base/Charger POS Multi-Interface
- BC4030: Base/Charger STD Multi-Interface
- CHR-GM40: Charging Only Base Station



Batteries/Battery Chargers

- RBP-GM40: Removable Battery Pack

Mounts/Stand

- HLD-G040-BK: Desk/Wall Holder, G040, Black
- HLD-G040-WH: Desk/Wall Holder, G040, White
- STD-AUTO-G040-BK: Smart Stand, G040, Black
- STD-AUTO-G040-WH: Smart Stand, G040, White
- STD-G040-BK: Basic Stand, G040, Dark
- STD-G040-WH: Basic Stand, G040, White



© 2009 Datalogic Scanning Inc.

All rights reserved. • Protected to the fullest extent under U.S. and international laws.
 • Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc.

Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries including the U.S.A. and the E.U. Datalogic Aladdin and Datalogic STAR Cordless System are trademarks of Datalogic Scanning Group S.r.l.

Gryphon is a trademark of Datalogic Scanning, Inc.

Other brands and product names may be trademarks of their respective owners.

Product specifications are subject to change without notice.

DS-GRYPHONIGM4100-ENA4 20091117

www.scanning.datalogic.com